

Graphenoil

TECHNICAL DATA SHEET

VETERAN OWNED SMALL BUSINESS



MADE IN USA

SN SAE 15W-40

UPDATED 12/24/2021

DESCRIPTION

Graphenoil Synthetic SN SAE 15W-40 is a premium quality, heavy-duty multi-grade oil for all season use in diesel and gasoline engines. Formulated with a premium additive package it is recommended especially for all on-highway service applications, and is also recommended for off-highway applications, especially where all-season use is desired.

APPLICATIONS

Recommended for North American trucks with turbo and non-turbo charged engines; for new EGR and low emission engines as well as older models.

Graphenoil engine oils are suited for use in heavy construction and mining equipment from leading makers such as Caterpillar and Komatsu.

Graphenoil engine oils contain select viscosity index improvers to provide easier cold weather starting and better high temperature protection demanded by modern high out-put engines.

MEETS & EXCEEDS

Graphenoil Full Synthetic motor oil meets and exceeds the following specifications and manufacturers' requirements: • DDC 93K218 • Caterpillar ECF-3 • Cummins CES 20081 • John Deere • Detroit Diesel Power Guard 93K218 • Mack EO-N Premium Plus 03 • Mercedes-Benz • Internationa • MB 228.31

PHYSICAL PROPERTIES

API Gravity @ 60°F	29.4°F
Viscosity @ 40°C	130 cst
Viscosity @ 100°C	15.5 cst
Viscosity Index	124
Flash Point	425°F
Pour Point	-33°C

METHOD OF USE

Treat current oil system according to manufacturer's specifications and owner's manual.
*Do not overfill.

STORAGE & HANDLING

Keep container closed until use. Keep out of direct sunlight and heat. Discard waste appropriately.

NOTES

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof.


In light of the foregoing, Graphenoil specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Graphenoil products. Graphenoil specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.

The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Graphenoil patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

TRADEMARK USAGE

Except as otherwise noted, all trademarks in this document are trademarks of Graphenoil in the USA and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office. Any and all Graphenoil marks may not be used without prior consent.

16310 HOLLISTER ST. HOUSTON, TX 77066



832.666.3143 | WWW.GRAPHENOIL.COM