

# TECHNICAL DATA SHEET





### DESCRIPTION

More than just boat wax. Graphenoil Marine Wax utilizes a nano technology formulation that penetrates deep into the pores of gel-coat, clear coat, and paint surfaces to provide a crystal clear, high gloss hardened polymer barrier. Outstanding protection against UV, salt and other environments throughout the season.

#### **APPLICATIONS**

Use on watercraft of any kind, including; RV's, aircraft, painted surfaces, gel-coat, metal and fiberglass. Also works great on cars, trucks, and commercial vehicles during the winter season when roads are salted. Other uses include; windows, glass shower doors, bathroom & kitchen fixtures to help prevent corrosion and water spots.

#### METHOD OF USE

Clean surface thouroughly. Shake well. Wipe on with a rag or sponge and remove with a high speed buffer set at 180-2100 RPM. Coat 6' sections at a time. Use wool polishing pads or yellow foam pads.

## **STORAGE & HANDLING**

Keep container closed until use. Keep out of direct sunlight and heat. Discard waste appropriately.

#### NOTES

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof.

In light of the foregoing, Graphenoil specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Graphenoil products. Graphenoil specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.

The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Graphenoil patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

### TRADEMARK USAGE

Except as otherwise noted, all trademarks in this document are trademarks of Graphenoil in the USA and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office. Any and all Graphenoil marks may not be used without prior consent.

