

Graphenoil

TECHNICAL DATA SHEET

VETERAN OWNED SMALL BUSINESS



MADE IN USA



TBN BOOSTER

UPDATED 05/25/2021

DESCRIPTION

GRAPHENOIL TBN BOOSTER (ASHLESS) IS USED TO INCREASE VISCOSITY OF HEAVY DUTY ENGINE OILS WITHOUT INCREASING THE SULFATE ASH CONTENT. GRAPHENOIL TBN BOOSTER ALSO IMPROVES THE OXIDATION LIFE OF HEAVY DUTY ENGINE OILS.

APPLICATIONS

FOR USE IN ALL MANUFACTURERS OF HEAVY DUTY ENGINES. 1% GRAPHENOIL TBN BOSTER ADDED WILL RAISE TBN BY 1.5 MG KOH/G.

FEATURES

- EXCELLENT OXIDATION PROTECTION
- EXCELLENT CORROSION PROTECTION
- GOOD DEMULSIBILITY PERFORMANCE
- SOLUABLE IN GROUP I-IV BASE OILS

PHYSICAL PROPERTIES

SPECIFIC GRAVITY @ 25°C	0.96
DENSITY, LBS/U.S. GAL @ 25°C	8.02
FLASH POINT PMCC	>150°C
VISCOSITY CST @ 40°C	130
VISCOSITY CST @ 100°C	7.8
POUR POINT	7°C
COLOR	4.5

METHOD OF USE

TREAT CURRENT OIL SYSTEM BY 1.5 MG KOH/G FOR EVERY 1.0 WT% ADDED, ACCORDING TO MANUFACTURER'S SPECIFICATIONS AND OWNER'S MANUAL. *DO NOT OVERFILL.

STORAGE & HANDLING

KEEP CONTAINER CLOSED UNTIL USE. KEEP OUT OF DIRECT SUNLIGHT AND HEAT. DISCARD WASTE APPROPRIATELY. STORE AT OR ABOVE 45°F TO PREVENT FREEZING.

NOTES

THE DATA CONTAINED HEREIN ARE FURNISHED FOR INFORMATION ONLY AND ARE BELIEVED TO BE RELIABLE. WE CANNOT ASSUME RESPONSIBILITY FOR THE RESULTS OBTAINED BY OTHERS OVER WHOSE METHODS WE HAVE NO CONTROL. IT IS THE USER'S RESPONSIBILITY TO DETERMINE SUITABILITY FOR THE USER'S PURPOSE OF ANY PRODUCTION METHODS MENTIONED HEREIN AND TO ADOPT SUCH PRECAUTIONS AS MAY BE ADVISABLE FOR THE PROTECTION OF PROPERTY AND OF PERSONS AGAINST ANY HAZARDS THAT MAY BE INVOLVED IN THE HANDLING AND USE THEREOF.


IN LIGHT OF THE FOREGOING, GRAPHENOIL SPECIFICALLY DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARISING FROM SALE OR USE OF GRAPHENOIL PRODUCTS. GRAPHENOIL SPECIFICALLY DISCLAIMS ANY LIABILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OF ANY KIND, INCLUDING LOST PROFITS.

THE DISCUSSION HEREIN OF VARIOUS PROCESSES OR COMPOSITIONS IS NOT TO BE INTERPRETED AS REPRESENTATION THAT THEY ARE FREE FROM DOMINATION OF PATENTS OWNED BY OTHERS OR AS A LICENSE UNDER ANY GRAPHENOIL PATENTS THAT MAY COVER SUCH PROCESSES OR COMPOSITIONS. WE RECOMMEND THAT EACH PROSPECTIVE USER TEST HIS PROPOSED APPLICATION BEFORE REPETITIVE USE, USING THIS DATA AS A GUIDE. THIS PRODUCT MAY BE COVERED BY ONE OR MORE UNITED STATES OR FOREIGN PATENTS OR PATENT APPLICATIONS.

TRADEMARK USAGE

EXCEPT AS OTHERWISE NOTED, ALL TRADEMARKS IN THIS DOCUMENT ARE TRADEMARKS OF GRAPHENOIL IN THE USA AND ELSEWHERE. ® DENOTES A TRADEMARK REGISTERED IN THE U.S. PATENT AND TRADEMARK OFFICE. ANY AND ALL GRAPHENOIL MARKS MAY NOT BE USED WITHOUT PRIOR CONSENT.

16310 HOLLISTER ST. HOUSTON, TX 77066



832.666.3143 | WWW.GRAPHENOIL.COM